

## 3U and 6U VPX Power Supplies



### 3U

- [VPX55H-3](#) DC/DC 500 Watts, +28 VDC input voltage and provides six outputs
- [VPX55-3HU](#) DC/DC - 400 watts Power Line Conditioner - 50 milliseconds of holdup time
- [VPX68-3](#) DC/DC - 400 Watts, Six Outputs with Holdup Time
- [VPX56-3HU](#) AC/DC - 400 Watts Power Line Conditioner - 50 milliseconds of holdup time
- [VPX57-31](#) DC/DC - 500-Watts +270 VDC input voltage
- [VPX57HS](#) DC/DC – 725-Watts +270 VDC input voltage

### 6U

- [VPX56H-6](#) 115 VAC 3 Phase or +270 VDC, 1, 000 Watts, VITA 62 I/O, Programmable, I2C, OverTemp, Current Share
- [VPX56H2-6](#) 115 VAC 3 Phase or +270 VDC, 1,400 Watts, VITA 62 I/O, Programmable, I2C, OverTemp, Current Share



### [Power Supply Selection Guide](#)

**For more information Contact TPT KK**

詳細はメール ( [sales.t@tptech.co.jp](mailto:sales.t@tptech.co.jp) ) でのお問い合わせもしくはホームページ ( <http://www.tptech.co.jp/> ) をご参照ください。

ティー・ピー・ティー株式会社

〒110-0008 東京都台東区池之端 1-6-13 ( 境会館 5F)

電話 : 03-5832-7350